

NBC03HRA

Polypropylene (PP)

Description:

NBC03HRA is a Polypropylene (PP) type H NEWCON thermoplastic olefin (TPO). It is a PP which has high rubber and high melt flow index for using in injection molding process or. The features are excellent cold impact, heat resistance, and good fluidity.

Typical applications;

Injection molding: Interior & exterior parts for automobile, polymer base for polymer compounding

Physical Properties:	Method	Unit	Value
Density	ISO1183	g/cm ³	0.90
Melt Flow Index (2.16 kg/230°C)	ISO1133	g/10min.	32
Tensile Strength at Yield	ISO 527-1	N/mm ²	21
Charpy Notched Impact Strength (at 23°C)	ISO179	kJ/m ²	12
Flexural Modulus (1% SECANT)	ISO178	MPa	1050
Heat Distortion Temperature @ 4.6 kg	ISO75	°C	90

Processing Technique

Processing Temperature : 190 – 240 °C

However, the actual processing conditions depend on mold design, power of machine, equipment and other environments.

Remark: The values presented on the above are typical laboratory average, not to be construed as specifications and may vary within moderate ranges. The applicability or the accuracy of this information or the suitability of our products cannot be guaranteed because the conditions of use on the part or our uses are beyond our control.