

AS103

Acrylonitrile Styrene (AS/SAN)

Description:

AS103 is a acrylonitrile styrene resin with natural color.

Typical applications;

Compounding: ABS, PC/ABS etc.

Physical Properties:	Method	Unit	Value
AN Content	ASTM D5291	%	24
Melt Flow Index (200 °C/5kg)	ASTM D1238	g/10min.	2.8
ΥΙ	ASTM D1925	_	9

Processing Technique

Drying Temperature: 80-85°C, 2-3 hrs.

Processing Temperature : 210-260°C

* * However, the actual processing conditions depend on mold design, power of machine, equipment and other environments. **

Remark: The values presented on the above are typical laboratory average, not to be construed as specifications and may vary within moderate ranges. The applicability or the accuracy of this information or the suitable of our products cannot be guaranteed because the conditions of use on the part or our uses are beyond our control.

REV. 20170601

บริษัท ไออาร์พีซี จำกัด (มหาชน) 555/2 ศูนย์เอนเนอร์ยี่คอมเพล็กซ์ อาการ บี ชั้น 6 ถนนวิกาวดีรับสิต แขวงอตุจักร เขตอตุจักร กรุงเทพฯ 10900 โกร. +66(0)2649-7000,66(0)2649-7777 แพ็กซ์: +66(0)2649-7002 IRPC Public Company Limited 555/2 Energy Complex Building B, oth Floor, Vibhavadi Rangsit Road, Chatuchak, Bangkok 10900 THAILAND. TEL:+66(0)2649-7000,66(0)2649-7777 FAX:+66(0)2649-7002 www.irpc.co.th, www.irpcmarket.com